

## KV 240

### UPVC/ALUMINIUM COMPOSITE WINDOW

- Thermal insulation with standard triple glazing ( $U_g = 0.95 \text{ W/m}^2\text{K}$ )  $U_w = 1.1 \text{ W/m}^2\text{K}$
- Best thermal insulation at low weight  **$U_w$  up to  $0.80 \text{ W/m}^2\text{K}$**  (with 3light glazing)
- Soundproofing up to 45 dB (with corresponding glazing)
- 71 mm construction depth
- Flush design outside and inside also with square-edged glass bead
- Integrated between the panes, therefore provides privacy and sun protection
- Narrow view width up to 102 mm
- Triple gasket system
- Fully concealed hardware available upon request
- FIX-O-ROUND technology
- 5 chamber system
- Locking parts screwed into steel – from a certain window size on



**I-tec Shading**

**I-tec Glazing**



#### QUADRUPLE PROTECTION

Thermal, sound, sun and privacy protection all in one window. No additional structural provision necessary. No extra fitting necessary for sun protection systems.



#### FLUSH DESIGN

With this innovative composite window in modern square-edged design, integration into the facade is possible on three sides. Inside square-edged glass bead available upon request.



#### I-TEC SHADING

Available upon request with photovoltaic blind, Venetian blind or Duette® with self-sufficient energy. Energy supply via integrated photovoltaic module, no extra fitting necessary, bi-directional wireless control.