

## KF 410

### UPVC & UPVC/ALUMINIUM WINDOW

- Thermal insulation with standard triple glazing SOLAR+ and highly thermally insulating edge seal ( $U_g = 0.6 \text{ W/m}^2\text{K}$ )  $U_w = 0.79 \text{ W/m}^2\text{K}$
- Best thermal insulation  $U_w$  up to **0.62 W/m<sup>2</sup>K** (with corresponding glazing)
- Soundproofing up to 45 dB (with corresponding glazing)
- 90 mm construction depth
- Triple gasket system
- Gasket colour outside black or light grey (only in UPVC/aluminium version)
- Fully concealed hardware
- Visible or concealed drainage
- FIX-O-ROUND technology
- Resistance class WK1 and WK2 untested (upon request)
- Standard security
- 5 chamber system with highly thermally insulating thermal foam (HCFC, HFC and FC free)
- Shortened aluminium attachment clad available upon request, for thermo-technical optimised construction connection



**I-tec** Glazing



#### UPVC VERSION

Along with the aluminium attachment clad version in all colours, the classic UPVC version in white is also available.



#### HARMONIC INTERIOR DESIGN

The rounded glass bead fits perfectly with the classic design style ambiente



#### OUTSIDE GASKETS

With the UPVC/aluminium version you can choose between black and light grey gaskets for the outside.