













| Material | Timber/aluminium | | | | | | |
|--|---|---|---|---|---|---|---|
| System |  |  |  |  |  |  |  |
| Style | studio | home pure | home soft | ambiente | home pure | home soft | ambiente |
| Design | flush | square-edged | profiled | profiled | square-edged | profiled | profiled |
| Thermal insulation  | ★★★★★ U _D = 0.58 W/m ² K | ★★★★★ U _D up to 0.73 W/m ² K | ★★★★★ U _D up to 0.73 W/m ² K | ★★★★★ U _D up to 0.73 W/m ² K | ★★★★★ U _D up to 0.74 W/m ² K | ★★★★★ U _D up to 0.74 W/m ² K | ★★★★★ U _D up to 0.74 W/m ² K |
| Soundproofing  | ★★★★★ up to 37 dB | ★★★★★ up to 33 dB | ★★★★★ up to 33 dB | ★★★★★ up to 33 dB | ★★★★★ up to 28 dB | ★★★★★ up to 28 dB | ★★★★★ up to 28 dB |
| Security  | ★★★★★ up to WK2 | ★★★★★ up to WK2 | ★★★★★ up to WK2 | ★★★★★ up to WK2 | ★★★★★ up to WK3 | ★★★★★ up to WK3 | ★★★★★ up to WK2 |
| Locking  | ★★★★★ multi-point locking | ★★★★★ multi-point locking | ★★★★★ multi-point locking | ★★★★★ multi-point locking | ★★★★★ multi-point locking | ★★★★★ multi-point locking | ★★★★★ multi-point locking |
| Profile construction depth (in mm)  | 121 | 85.5 | 93 | 93 | 85.5 | 93 | 93 |
| Page reference | page 13 | page 35 | page 85 | page 127 | page 47 | page 95 | page 135 |