

KV 240

UPVC/ALUMINIUM COMPOSITE WINDOW

- Thermal insulation with standard triple glazing ($U_g = 0.95 \text{ W/m}^2\text{K}$) $U_w = 1.1 \text{ W/m}^2\text{K}$
- Best thermal insulation at low weight
 U_w up to $0.80 \text{ W/m}^2\text{K}$ (with 3light glazing)
- Soundproofing up to 45 dB (with corresponding glazing)
- 71 mm construction depth
- Flush design outside and inside also with square glass bead
- Integrated between the panes, therefore provides privacy and sun protection – i-tec shading available upon request.
- Fully concealed hardware upon request
- Narrow view width up to 102 mm
- FIX-O-ROUND technology
- 5 chamber system
- Triple gasket system
- Frameless sash facilitates easier cleaning and maintenance of the glass
- Standard security



I-tec Shading

I-tec Glazing



QUADRUPLE PROTECTION

Thermal, sound, sun and privacy protection all in one window. No additional structural provision necessary. No extra fitting necessary for sun protection systems.



FLUSH DESIGN

With this innovative composite window in modern square-edged design, integration into the facade is possible on three sides. Inside square-edged glass bead available upon request.



I-TEC SHADING

Available upon request with photovoltaic blind, Venetian blind or Duette with self-sufficient energy. Energy supply via integrated photovoltaic module, no extra fitting necessary, bi-directional wireless control.